

10. Equilibrado hidráulico dinámico de instalaciones

10.1. Cartuchos metálicos ALPHA de ajuste de caudal

Cartuchos TIPO 30 para válvulas de DN25L-50

FRESE - Rango de presión: 12-600 kPa.

REFERENCIA	CAUDAL		Mín. ΔP kPa	Kv	CÓDIGO
	l/h	l/s			
49-33073	674	0,188	12	1,95	0133073
49-33082	861	0,239	12	2,49	0133082
49-33089	1020	0,283	12	2,94	0133089
49-33094	1136	0,315	12	3,28	0133094
49-33096	1190	0,331	12	3,44	0133096
49-33098	1272	0,353	13	3,53	0133098
49-33102	1349	0,375	13	3,74	0133102
49-33107	1485	0,413	13	4,12	0133107
49-33111	1567	0,435	14	4,19	0133111
49-33112	1631	0,453	14	4,36	0133112
49-33118	1815	0,504	14	4,85	0133118
49-33124	2001	0,556	15	5,17	0133124
49-33125	2044	0,568	16	5,11	0133125
49-33129	2171	0,603	16	5,43	0133129
49-33132	2271	0,631	17	5,51	0133132
49-33135	2380	0,661	17	5,77	0133135
49-33138	2498	0,694	18	5,89	0133138
49-33142	2639	0,733	18	6,22	0133142
49-33148	2871	0,797	19	6,59	0133148
49-33156	3191	0,886	21	6,96	0133156
49-33161	3407	0,946	22	7,26	0133161
49-33163	3486	0,968	22	7,43	0133163

Cartuchos TIPO 40 para válvulas de DN25L-50

FRESE - Rango de presión: 20-600 kPa.

REFERENCIA	CAUDAL		Mín. ΔP kPa	Kv	CÓDIGO
	l/h	l/s			
49-44148	3634	1,009	20	8,13	0144148
49-44152	3681	1,023	21	8,03	0144152
49-44156	4088	1,136	21	8,92	0144156
49-44164	4315	1,199	21	9,42	0144164
49-44168	4542	1,262	22	9,68	0144168
49-44173	4769	1,325	22	10,17	0144173
49-44176	4996	1,388	23	10,42	0144176
49-44182	5450	1,514	24	11,12	0144182
49-44191	5905	1,640	25	11,81	0144191
49-44194	6539	1,816	26	12,82	0144194
49-44200	6813	1,893	27	13,11	0144200
49-44205	7267	2,019	28	13,73	0144205
49-44211	7721	2,145	30	14,10	0144211
49-44217	8176	2,271	31	14,68	0144217
49-44222	8630	2,397	33	15,02	0144222
49-44229	9084	2,523	34	15,58	0144229
49-44235	9538	2,650	36	15,90	0144235
49-44241	9990	2,776	38	16,21	0144241
49-44248	10445	2,902	40	16,51	0144248
49-44250	10900	3,028	42	16,82	0144250
49-44262	11355	3,154	44	17,12	0144262



App Frese valves



www.frese.es